



Works Approval

Works approval number	W6859/2023/1
Works approval holder	Pilgangoora Operations Pty Ltd
ACN	616 560 395
Registered business address	Level 2, 146 Colin Street WEST PERTH WA 6005
DWER file number	DER2023/000562
Duration	19/03/2024 to 18/03/2029
Date of issue	19/03/2024
Premises details	Pilgangoora Operations Mining tenements M45/1230 and M45/1260 MARBLE BAR WA 6760 As depicted in Schedule 1

Prescribed premises category description (Schedule 1, <i>Environmental Protection Regulations 1987</i>)	Assessed production / design capacity
Category 5: Processing or beneficiation of metallic or non-metallic ore	4,000,000 tonnes per annum

This works approval is granted to the works approval holder, subject to the attached conditions, on 19 March 2024, by:

**MANAGER, RESOURCE INDUSTRIES
REGULATORY SERVICES**
an officer delegated under section 20 of
the *Environmental Protection Act 1986* (WA)

Works approval history

Date	Reference number	Summary of changes
19/03/2024	W6859/2023/1	Works approval granted.

Interpretation

In this works approval:

- (a) the words ‘including’, ‘includes’ and ‘include’ in conditions mean “including but not limited to”, and similar, as appropriate;
- (b) where any word or phrase is given a defined meaning, any other part of speech or other grammatical form of that word or phrase has a corresponding meaning;
- (c) where tables are used in a condition, each row in a table constitutes a separate condition;
- (d) any reference to an Australian or other standard, guideline, or code of practice in this works approval:
 - (i) if dated, refers to that particular version; and
 - (ii) if not dated, refers to the latest version and therefore may be subject to change over time;
- (e) unless specified otherwise, any reference to a section of an Act refers to that section of the EP Act; and
- (f) unless specified otherwise, all definitions are in accordance with the EP Act.

NOTE: This works approval requires specific conditions to be met but does not provide any implied authorisation for other emissions, discharges, or activities not specified in this works approval.

Works approval conditions

The works approval holder must ensure that the following conditions are complied with:

Construction phase

General

1. The works approval holder must manage stormwater generated during the construction/installation of the infrastructure specified in Table 1, by capturing all sediment laden stormwater within sediment basins, prior to release to the environment.

Infrastructure and equipment

2. The works approval holder must:
 - (a) construct the critical containment infrastructure;
 - (b) in accordance with the corresponding design and construction requirements; and
 - (c) at the corresponding infrastructure location;
 as set out in Table 1.

Table 1: Critical containment infrastructure design and construction requirements

Item	Infrastructure	Design and construction / installation requirements	Infrastructure location
1.	Tailings Storage Facility 3 (TSF3) Stage 1	(a) Embankments to be constructed in accordance with the design details shown in Figure 4 and Figure 8 of Schedule 2. (b) Embankment settlement pins to be installed at regular intervals along the embankment crest and constructed in accordance with the design details shown in Figure 12 of Schedule 2. (c) Install vibrating wire piezometers (VWP) in accordance with the design details shown in Figure 12 of Schedule 2. VWP fitted with instrument readout stations (to download data to a central storage location). (d) Embankment height not to exceed RL 180.2m as shown in Figure 4 and Figure 8 of Schedule 2. (e) Constructed so a minimum freeboard of 500 mm is maintained following a 1% AEP ,72-hour rainfall event. (f) Freeboard markers placed on embankment to allow visual freeboard inspection. (g) Underdrainage system constructed/ installed in accordance with the design details shown in Figure 5, Figure 6 and Figure 7 of Schedule 2. (h) Decant pump platform and access	As shown in Figure 2 of Schedule 1

Item	Infrastructure	Design and construction / installation requirements	Infrastructure location
		<p>causeway located as shown in Figure 3 of Schedule 2 and constructed in accordance with design details shown in Figure 9 of Schedule 2.</p> <p>(i) Distribution pipeline fitted with spigot offtakes located at regularly spaced intervals (nominally every 25 m) along the embankment crest. Spigot clamps installed on each offtake hose allowing the deposition location to be controlled.</p> <p>(j) Tailings delivery pipeline to be connected to the distribution pipeline on the embankment crest. Pipework to be located on the upstream side of the embankment crest.</p> <p>(k) Decant pipeline to be contained on the upstream crest of the TSF and within a bunded easement to the decant water storage pond.</p>	
2.	Tailings Storage Facility 3 (TSF3) Stage 2	<p>(a) Embankments to be constructed in accordance with the design details shown in Figure 20 of Schedule 2</p> <p>(b) Embankment settlement pins to be installed at regular intervals along the embankment crest and constructed in accordance with the design details shown in Figure 12 of Schedule 2.</p> <p>(l) Embankment height not to exceed RL 184.1 m as shown in Figure 8 and Figure 20 of Schedule 2.</p> <p>(c) Constructed so a minimum freeboard of 500 mm is maintained following a 1% AEP, 72-hour rainfall event.</p> <p>(d) Freeboard makers placed on embankment to allow visual freeboard inspection.</p> <p>(m) Decant pump platform and access causeway located as shown in Figure 19 of Schedule 2 and constructed in accordance with design details shown in Figure 20 of Schedule 2.</p> <p>(n) Distribution pipeline fitted with spigot offtakes located at regularly spaced intervals (nominally every 25 m) along the embankment crest. Spigot clamps installed on each offtake hose allowing the deposition location to be controlled.</p> <p>(o) Tailings delivery pipeline to be connected to the distribution pipeline on the embankment crest. Pipework to be located on the upstream side of the embankment</p>	As shown in Figure 2 of Schedule 1

Item	Infrastructure	Design and construction / installation requirements	Infrastructure location
		<p>crest.</p> <p>(p) Decant pipeline to be contained on the upstream crest of the TSF and within a bunded easement to the decant water storage pond.</p>	
3.	TSF3 decant water storage pond	<p>(a) Constructed in accordance with the design details shown in Figure 10 of Schedule 2.</p> <p>(b) Constructed with a capacity to store a maximum of 50 ML of collected decant water.</p> <p>(c) Constructed so a minimum freeboard of 500 mm is maintained following a 1% AEP, 72-hour rainfall event.</p> <p>(d) Embankment height not to exceed RL 180.8m.</p>	As shown in Figure 2 of Schedule 1 and Figure 3 of Schedule 2
4.	NLO Stage 5 embankment lift	<p>(a) Embankments to be constructed in accordance with the design details shown in Figure 14, Figure 15 and Figure 16 of Schedule 2.</p> <p>(b) Embankment height not to exceed RL 192.1m.</p> <p>(c) Constructed so a minimum freeboard of 500 mm is maintained following a 1% AEP, 72-hour rainfall event.</p> <p>(d) Upstream spigot deposition of tailings from the Stage 5 embankment crest.</p> <p>(e) The Stage 5 decant raise to comprise of 1.8 m diameter slotted precast concrete decant tower sections surrounded by free-draining coarse rockfill. Constructed in accordance with the design details shown in Figure 17 of Schedule 2.</p> <p>(f) Extend embankment piezometer cables to ensure the continued monitoring of the phreatic surface.</p> <p>(g) Install embankment settlement pins at regular intervals along the Stage 5 embankment crest to monitor embankment movements.</p>	As shown in Figure 2 Schedule 1 and Figure 13 of Schedule 2
5.	New and reinstalled tailings delivery pipelines and decant return water pipelines	<p>(a) Pipelines constructed according to Australian Standards AS/NZS 2033, 4129, 4130 and 4131 for polyethylene pipes.</p> <p>(b) Pipelines located within bunded corridors for secondary spillage containment.</p> <p>(c) Equipped with leakage detection (flow and pressure monitoring) with automatic cut-outs in the event of a pipeline failure.</p>	Within the Premises boundary shown in Figure 1 of Schedule 1

Item	Infrastructure	Design and construction / installation requirements	Infrastructure location
		<p>(d) Where pipelines are constructed within road corridors, those roads must be bunded by earthen windrows to contain pipelines leaks.</p> <p>(e) Following construction and prior to time limited operations:</p> <ul style="list-style-type: none"> (i) Pipelines must be leak tested. (ii) All flow meters to be calibrated; and (iii) All pressure meters to be calibrated. 	

Construction of groundwater monitoring wells

3. The works approval holder must design, construct, and install groundwater monitoring wells in accordance with the requirements specified in Table 2 .

Table 2: Infrastructure requirements – groundwater monitoring wells

Infrastructure	Design, construction, and installation requirements	Monitoring well location(s)	Timeframe
<p>Groundwater monitoring well(s):</p> <p>TSF3MB001_D TSF3MB001_S TSF3MB002_D TSF3MB002_S TSF3MB003_D TSF3MB003_S TSF3MB004_D TSF3MB004_S TSF3MB005_D TSF3MB005_S TSF3MB006_D TSF3MB006_S TSF3MB007_D TSF3MB007_S TSF3MB008_D TSF3MB008_S</p>	<p><u>Well design and construction:</u></p> <p>Designed and constructed in accordance with <i>ASTM D5092/D5092M-16: Standard practice for design and installation of groundwater monitoring bores</i>.</p> <p>Well screens must target the part, or parts, of the aquifer most likely to be affected by contamination¹. Where temporary/seasonal perched features are present, wells must be nested, and the perched features individually screened. The screened interval should be no longer than 6 metres.</p> <p><u>Logging of borehole:</u></p> <p>Soil samples must be collected and logged during the installation of the monitoring wells.</p> <p>A record of the geology encountered during drilling must be described and classified in accordance with the Australian Standard Geotechnical Site Investigations AS1726.</p> <p>Any observations of staining / odours or other indications of contamination must be included in the bore log.</p> <p><u>Well construction log:</u></p> <p>Well construction details must be documented within a well construction log to demonstrate compliance with <i>ASTM D5092/D5092M-16</i>. The construction logs shall include elevations of the top of casing position to be used as the reference point for water-level</p>	<p>As depicted in Figure 11 of Schedule 2. Map of groundwater monitoring well locations.</p> <p>An allowance of +/- 25 m for each groundwater monitoring well location is permitted.</p>	<p>Must be constructed, developed (purged), and determined to be operational by no later than 30 calendar days prior to commencement of time limited operations.</p>

Infrastructure	Design, construction, and installation requirements	Monitoring well location(s)	Timeframe
	<p>measurements, and the elevations of the ground surface protective installations.</p> <p><u>Well development:</u> All installed monitoring wells must be developed after drilling to remove fine sand, silt, clay and any drilling mud residues from around the well screen to ensure the hydraulic functioning of the well. A detailed record should be kept of well development activities and included in the well construction log.</p> <p><u>Installation survey:</u> the vertical (top of casing) and horizontal position of each monitoring well must be surveyed and subsequently mapped by a suitably qualified surveyor.</p> <p><u>Well network map:</u> a well location map (using aerial image overlay) must be prepared and include the location of all monitoring wells in the monitoring network and their respective identification numbers.</p>		

Note 1: refer to Section 8 of Schedule B2 of the *Assessment of Site Contamination NEPM* for guidance on well screen depth and length.

Groundwater monitoring prior to time limited operations

4. The works approval holder must conduct groundwater monitoring in accordance with the requirements specified in Schedule 3 and:
- at the corresponding monitoring location;
 - for the corresponding parameters;
 - in the corresponding unit;
 - at no less than the corresponding frequency;
 - using the corresponding method,
- as set out in Table 3

Table 3 Groundwater monitoring of ambient concentrations

Monitoring location	Parameter	Unit	Averaging period	Frequency	Method
Groundwater monitoring well(s)	Standing Water Level ¹	mbgl	Spot sample	A single sampling event undertaken prior to commencement of time limited operations	AS/NZS 5667.1 AS/NZS 5667.11
TSF3MB001_D	pH ¹	pH units			
TSF3MB001_S	Electrical Conductivity	µS/cm			
TSF3MB002_D	Total Dissolved				
TSF3MB002_S					
TSF3MB003_D					

Monitoring location	Parameter	Unit	Averaging period	Frequency	Method
TSF3MB003_S TSF3MB004_D TSF3MB004_S TSF3MB005_D TSF3MB005_S TSF3MB006_D TSF3MB006_S TSF3MB007_D TSF3MB007_S TSF3MB008_D TSF3MB008_S as depicted in Figure 11 of Schedule 2. Map of groundwater monitoring well locations.	Solids	mg/L			
	Total Alkalinity as CaCO ₃				
	Carbonate Alkalinity as CO ₃				
	Bicarbonate Alkalinity as HCO ₃				
	Fluoride by ISE				
	Chloride, Cl				
	Sulfate, SO ₄				
	Nitrite, NO ₂				
	Nitrate, NO ₃				
	Sodium, Na				
	Potassium, K				
	Calcium, Ca				
	Magnesium, Mg				
	Total Hardness by Calculation				
	Phosphorus, P				
	Total Phosphorus				
	Total Nitrogen				
	Aluminium, Al				
	Arsenic, As				
	Cadmium, Cd				
	Cobalt, Co				
	Chromium, Cr				
	Copper, Cu				
	Iron, Fe				

Monitoring location	Parameter	Unit	Averaging period	Frequency	Method
	Lithium, Li				
	Manganese, Mn				
	Nickel, Ni				
	Lead, Pb				
	Zinc, Zn				
	Barium, Ba				
	Boron, B				
	Mercury, Hg				
	Molybdenum, Mo				
	Antimony, Sb				
	Selenium, Se				
	Silicon, Si				
	Tin, Sn				
	Vanadium, V				
	Uranium, U				
	Thorium, Th				
	Bismuth, Bi				
	Nobium, Nb				
	Thallium, Tl				
	Caesium, Cs				
	Rubidium, Rb				
	Radium-266	Bq/L			
	Radium-228				

Note 1: In-field non-NATA accredited analysis permitted.

5. All sample analysis must be undertaken by laboratories with current accreditation from the National Association of Testing Authorities (NATA) for the relevant parameters, unless otherwise specified in condition 4.

Critical containment infrastructure report

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)

6. The works approval holder must within 90 calendar days of the Critical Containment Infrastructure identified by condition 2 being constructed:
 - (a) undertake an audit of their compliance with the requirements of condition 2; and
 - (b) prepare and submit to the CEO a Critical Containment Infrastructure Report on that compliance
7. The Critical Containment Infrastructure Report required by condition 6 must include as a minimum the following:
 - (a) certification by a suitably qualified geotechnical engineer that each item of critical containment infrastructure or component thereof, as specified in condition 2, has been built and installed in accordance with the requirements specified in condition 2;
 - (b) as constructed plans and a detailed site plan showing the location and dimensions for each item of critical containment infrastructure or component thereof, as specified in condition 2;
 - (c) photographic evidence of the installation of the infrastructure; and
 - (e) be signed by a person authorised to represent the works approval holder and contains the printed name and position of that person;

Compliance reporting (well construction and ambient groundwater monitoring)

8. The works approval holder must, within 60 calendar days of the monitoring wells being constructed, submit to the CEO a construction report evidencing compliance with the requirements of condition 3.
9. The works approval holder must submit to the CEO, a monitoring report demonstrating compliance with condition 4, and must include:
 - (a) a clear statement of the scope of work carried out;
 - (b) a description of the field methodologies employed;
 - (c) a summary of the field and laboratory quality assurance / quality control (QA/QC) program (as outlined in Schedule 3);
 - (d) copies of the field monitoring records and field QA/QC documentation;
 - (e) an assessment of reliability of field procedures and laboratory results;
 - (f) a tabulated summary of results, as well as all raw data provided in an accompanying Microsoft Excel spreadsheet digital document/file (or a compatible equivalent digital document/file), with all results being clearly referenced to laboratory certificates of analysis;
 - (g) a diagram with aerial image overlay showing all monitoring locations and depicting groundwater level contours, flow direction and hydraulic gradient (relevant site features including discharge points and other potential sources of contamination must also be shown); and
 - (h) an interpretive summary and assessment of the results against relevant assessment levels for water, as published in the Guideline Assessment and management of contaminated sites.

Note 1: General guidance on report presentation can be found in the Department's *Guideline: Assessment and management of contaminated sites*.

Time limited operations phase

Commencement and duration (critical containment infrastructure)

- 10.** The works approval holder may only commence time limited operations for an item of critical containment infrastructure identified in condition 2:
- where the CEO has notified the works approval holder that the Critical Containment Infrastructure Report for that item of infrastructure as required by condition 6 and 7 meets the requirements of those conditions; or
 - where at least 45 business days have passed after the Critical Containment Infrastructure Report for that item of infrastructure as required by condition 6 and 7 has been submitted to the CEO.
- 11.** The works approval holder may conduct time limited operations for an item of infrastructure specified in condition 12 (as applicable):
- for a period not exceeding 180 calendar days from the day the works approval holder meets the requirements of condition 10 for that item of infrastructure; or
 - until such time as a licence for that item of infrastructure is granted in accordance with Part V of the Environmental Protection Act 1986, if one is granted before the end of the period specified in condition 11(a)

Time limited operations requirements and emission limits

- 12.** During time limited operations, the works approval holder must ensure that the premises infrastructure and equipment listed in Table 4 and located at the corresponding infrastructure location is maintained and operated in accordance with the corresponding operational requirement set out in Table 4.

Table 4: Infrastructure and equipment requirements during time limited operations

item	Site infrastructure and equipment	Operational requirement	Infrastructure location
1.	TSF3 Stage 1	<ol style="list-style-type: none"> To be maintained as per the design and construction/installation requirements in condition 2 The supernatant pond is maintained at the decant tower location at the waste dump side (remote from the main embankment) Visual inspections daily and following a 1% AEP, 72-hour rainfall event to check: <ul style="list-style-type: none"> A minimum freeboard of 500 mm is being maintained Location and size of decant pond (in hectares and expressed as a total percentage of the surface area of the TSF) Change in seepage conditions or sudden change in water level Signs of erosion 	As shown in Figure 2 of Schedule 1 and Figure 3 of Schedule 2

item	Site infrastructure and equipment	Operational requirement	Infrastructure location
2.	NLO TSF Stage 5	(a) To be maintained as per the design and construction/installation requirements in condition 2 (b) Visual inspections daily and following a 1% AEP 72-hour, rainfall event to check: <ul style="list-style-type: none"> • A minimum freeboard of 500 mm is being maintained • Location and size of decant pond (in hectares and expressed as a total percentage of the surface area of the TSF) • Change in seepage conditions or sudden change in water level • Signs of erosion 	As shown in Figure 2 of Schedule 1 and Figure 13 of Schedule 2
3.	Decant water storage pond	(a) To be maintained as per the design and construction/installation requirements in condition 2 (b) Visual inspections daily and following a 1% AEP. 72-hour rainfall event to check freeboard capacity and for any signs of erosion.	As shown in Figure 2 of Schedule 1 and Figure 3 of Schedule 2
4.	Pipelines carrying tailings and decant return water	(a) To be maintained as per the design and construction/installation requirements in condition 2 (b) Visual inspections every 24 hours when in operation to check the integrity of pipelines and bunding	Not applicable
5.	Vibrating wire piezometers (VWP)	(a) Fortnightly inspections to ensure integrity of VWPs and to ensure telemetry data is downloading to a central storage location	Within TSF3 and NLO Stage 5 embankments as determined by the design engineer specifications

Emissions and discharges

13. The works approval holder must ensure that the emissions specified in Table 5, are discharged only from the corresponding discharge point and only at the corresponding discharge point location.

Table 5: Authorised discharge points

Emission	Discharge point	Discharge point location
Tailings from the onsite Ngungaju Plant and the Pilgangoora Lithium-Tantalum Project (L9056)	NLO TSF Stage 5	As shown in Figure 2 of Schedule 1 and Figure 13 of Schedule 2
	TSF3	TSF3 as shown in Figure 2 of Schedule 1 and Figure 3 of Schedule 2

Tailings characterisation

14. During the first 60 calendar days of time limited operations, the works approval holder must undertake at least one kinetic test on a sample of material that is collected from the TSF3. To obtain a statistically representative sample of this material, the works approval holder must undertake the sampling in accordance with the following procedure:
- Collect a minimum 100 g sample of tailings material from every sixth tailings discharge spigot to obtain a total of 30 separate samples.
 - Combine the samples into a mine-dump composite sample; and
 - Dry sieve the mine-dump composite sample to ≤ 2 mm (final composite sample should weigh at least 1,000 g after sieving).
15. The results from the kinetic test required in condition 14 shall be collated in excel format and provided in a report to the CEO no more than 60 calendar days after sample collection.

Groundwater monitoring during time limited operations

16. The works approval holder must conduct groundwater monitoring in accordance with the requirements specified in Schedule 3 and:
- at the corresponding monitoring location;
 - for the corresponding parameters;
 - with the corresponding limit;
 - in the corresponding unit;
 - at no less than the corresponding frequency;
 - using the corresponding method,
- as set out in Table 6.

Table 6: Groundwater monitoring during time limited operations

Monitoring well location	Parameter	Triggers management action	Limit	Unit ²	Frequency	Method
Groundwater monitoring well(s) TSF3MB001_D TSF3MB001_S TSF3MB002_D TSF3MB002_S TSF3MB003_D TSF3MB003_S TSF3MB004_D TSF3MB004_S TSF3MB005_D TSF3MB005_S TSF3MB006_D TSF3MB006_S TSF3MB007_D TSF3MB007_S TSF3MB008_D	Standing water level	6	4	mbgl	A single sampling event undertaken between 30 and 60 calendar days following commencement of time limited operations (specifically tailings deposition into TSF3). AND A single sampling event undertaken	AS/NZS 5667.1 & AS/NZS 5667.11
	pH ¹	-	-	pH units		
	Electrical conductivity (EC)			µS/cm		
	Total Dissolved Solids			mg/L		
	Total Alkalinity as CaCO ₃					
	Carbonate Alkalinity as CO ₃					
	Bicarbonate Alkalinity as					

Monitoring well location	Parameter	Triggers management action	Limit	Unit ²	Frequency	Method
TSF3MB008_S as depicted in Figure 11 of Schedule 2. Map of groundwater monitoring well locations.	HCO ₃				between 120 and 180 calendar days following commencement of time limited operations (specifically tailings deposition into TSF3).	
	Fluoride by ISE					
	Chloride, Cl					
	Sulfate, SO ₄					
	Nitrite, NO ₂					
	Nitrate, NO ₃					
	Sodium, Na					
	Potassium, K					
	Calcium, Ca					
	Magnesium, Mg					
	Total Hardness by Calculation					
	Phosphorus, P					
	Total Phosphorus					
	Total Nitrogen					
	Aluminium, Al					
	Arsenic, As					
	Cadmium, Cd					
	Cobalt, Co					
	Chromium, Cr					
	Copper, Cu					
	Iron, Fe					
	Lithium, Li					
	Manganese, Mn					
	Nickel, Ni					
	Lead, Pb					
	Zinc, Zn					
	Barium, Ba					
	Boron, B					
	Mercury, Hg					
	Molybdenum, Mo					
	Antimony, Sb					
	Selenium, Se					
	Silicon, Si					

Monitoring well location	Parameter	Triggers management action	Limit	Unit ²	Frequency	Method
	Tin, Sn					
	Vanadium, V					
	Uranium, U					
	Thorium, Th					
	Bismuth, Bi					
	Nobium, Nb					
	Thallium, Tl					
	Caesium, Cs					
	Rubidium, Rb					
	Radium-266			Bq/L		
	Radium-228					

Note 1: In-field non-NATA accredited analysis permitted.

Note 2: The limits of reporting must be set to allow comparison with relevant assessment levels.

17. All sample analysis must be undertaken by laboratories with current accreditation from the National Association of Testing Authorities (NATA) for the relevant parameters, unless otherwise specified in condition 16.
18. The works approval holder must record, investigate, take corrective action and report to the CEO within 14 calendar days, in the event of a parameter in Condition 16 exceeding the corresponding limit or management action trigger.
19. The works approval holder must include the following information in the report referred to in condition 18 in relation to any exceedances of any limit identified in that condition:
 - (a) the nature of the exceedance;
 - (b) the time and date when the exceedance occurred;
 - (c) whether any environmental impact occurred as a result of the exceedance and, if so, what that impact was and where the impact occurred;
 - (d) the details of the management action(s) taken pursuant with condition 18 in response to the exceedance;
 - (e) the details and result of any investigation undertaken into the cause of the exceedance; and
 - (f) what action has been taken, or will be taken, to prevent the exceedance occurring again and for the purpose of minimising the likelihood of pollution or environmental harm.

Groundwater monitoring reporting requirements

20. The works approval holder must submit to the CEO, a monitoring report demonstrating their compliance with condition 16, and must include:
 - (a) a clear statement of the scope of work carried out;
 - (b) a description of the field methodologies employed;

- (c) a summary of the field and laboratory quality assurance / quality control (QA/QC) program (as specified in Schedule 3);
- (d) copies of the field monitoring records and field QA/QC documentation;
- (e) an assessment of reliability of field procedures and laboratory results;
- (f) a tabulated summary of results, as well as all raw data provided in an accompanying Microsoft Excel spreadsheet digital document/file (or a compatible equivalent digital document/file), with all results being clearly referenced to laboratory certificates of analysis;
- (g) a diagram with aerial image overlay showing all monitoring locations and depicting groundwater level contours, flow direction and hydraulic gradient (relevant site features including discharge points and other potential sources of contamination must also be shown);
- (h) an interpretive summary and assessment of the results against relevant assessment levels for water, as published in the Guideline Assessment and management of contaminated sites;
- (i) an interpretive summary and assessment of results against previous monitoring results; and
- (j) trend graphs to provide a graphical representation of historical results and to support the interpretive summary.

Note 1: General guidance on report presentation can be found in the Department's *Guideline: Assessment and management of contaminated sites*.

Water balance monitoring

- 21.** The works approval holder must review and assess the water balance for the TSF3 each monthly period, and (as a minimum) record the following information:
- (a) site rainfall (as determined by an on-site weather station);
 - (b) evaporation rate (as determined by an on-site weather station);
 - (c) decant water recovery volumes;
 - (d) volume of tailings deposited; and
 - (e) estimate of seepage losses.

Time limited operations - compliance reporting

- 22.** The works approval holder must submit to the CEO a report on the time limited operations within 30 calendar days of the completion date of time limited operations.
- 23.** The works approval holder must ensure the report required by condition 22 includes the following:
- (a) a summary of the time limited operations, including timeframes and amount of tailings discharged and material processed;
 - (b) a summary of monitoring results obtained under condition 4, 16 and 21;
 - (c) a summary of the environmental performance of all infrastructure as constructed or installed; and
 - (d) where the manufacturer's design specifications and the conditions of this works approval have not been met, what measures will the works approval holder take to meet them, and what timeframes will be required to implement those measures.

Records and reporting (general)

- 24.** The works approval holder must record the following information in relation to complaints received by the works approval holder (whether received directly from a complainant or forwarded to them by the Department or another party) about any alleged emissions from the premises:
- (a) the name and contact details of the complainant, (if provided);
 - (b) the time and date of the complaint;
 - (c) the complete details of the complaint and any other concerns or other issues raised; and
 - (d) the complete details and dates of any action taken by the works approval holder to investigate or respond to any complaint.
- 25.** The works approval holder must maintain accurate and auditable books including the following records, information, reports, and data required by this works approval:
- (a) the works conducted in accordance with condition(s) 2 and 3 ;
 - (b) any maintenance of infrastructure that is performed in the course of complying with condition 12;
 - (c) monitoring programmes undertaken in accordance with condition(s) 4, 16 and 21; and
 - (d) complaints received under condition 24.
- 26.** The books specified under condition 25 must:
- (a) be legible;
 - (b) if amended, be amended in such a way that the original version(s) and any subsequent amendments remain legible and are capable of retrieval;
 - (c) be retained by the works approval holder for the duration of the works approval; and
 - (d) be available to be produced to an inspector or the CEO as required.

Definitions

In this works approval, the terms in Table 7 have the meanings defined.

Table 7: Definitions

Term	Definition
AEP	means annual exceedance probability (used for design events (rainfalls and floods))
ARI	average recurrence interval
Assessment of Site Contamination NEPM	means the National Environment Protection (Assessment of Site Contamination) Measure 1999, as amended from time to time
Guideline: Assessment and management of contaminated sites"	means the document titled <i>Assessment and management of contaminated sites</i> (Department of Water and Environmental Regulation, November 2021), as amended from time to time
AS1726	means the Australian Standard AS1726 <i>Geotechnical Site Investigations</i>
AS/NZS 2033	means the Australian Standard AS/NZS 2033: Installation of polyethylene pipe systems
AS/NZS 4129	means the Australian Standard AS/NZS 4129: fittings for polyethylene (PE) pipes for pressure applications
AS/NZS 4130	means the Australian Standard AS/NZS 4130 Polyethylene pipes for pressure applications
AS/NZS 4131	means the Australian Standard AS/NZS 4131 Polyethylene compounds for pressure pipes and fittings.
AS/NZS 5667.1	means the Australian Standard AS/NZS 5667.1 <i>Water Quality – Sampling – Guidance on the design of sampling programs, sampling techniques and the preservation and handling of samples.</i>
AS/NZS 5667.11	means the Australian Standard AS/NZS 5667.11 <i>Water Quality - Sampling Guidance on sampling of groundwaters</i>
ASTM D5092/D5092M-16	means the ASTM international standard for <i>Standard practice for design and installation of groundwater monitoring wells</i> (Designation: ASTM D5092/D5092M-16).
books	has the same meaning given to that term under the EP Act.
CEO	means Chief Executive Officer. CEO for the purposes of notification means: Director General Department administering the <i>Environmental Protection Act 1986</i> Locked Bag 10 Joondalup DC WA 6919 info@dwer.wa.gov.au

Term	Definition
critical containment infrastructure	means the items of infrastructure listed in condition 2.
Critical Containment Infrastructure Report	means a report to satisfy the CEO that works of critical containment infrastructure have been constructed in accordance with the works approval.
Department	means the department established under section 35 of the <i>Public Sector Management Act 1994</i> and designated as responsible for the administration of Part V Division 3 of the EP Act.
discharge	has the same meaning given to that term under the EP Act.
emission	has the same meaning given to that term under the EP Act.
EP Act	<i>Environmental Protection Act 1986</i> (WA).
EP Regulations	<i>Environmental Protection Regulations 1987</i> (WA).
Freeboard	Means the distance between the maximum water surface elevation and the top of the retaining banks or structures at their lowest point
Kinetic Test	Kinetic test means a test undertaken in accordance with US EPA Method 1627: <i>Kinetic Test Method for the Prediction of Mine Drainage Quality</i> , December 2011
L9056	means EP Act Licence L9056/2017/1 for the Pilgangoora Lithium – Tantalum Project
monthly period	means a one-month period commencing from the first day of a month until the last day of that same month.
premises	the premises to which this works approval applies, as specified at the front of this works approval and as shown on the premises map in Schedule 1 to this works approval.
prescribed premises	has the same meaning given to that term under the EP Act.
suitably qualified geotechnical engineer	means a competent professional who: <ul style="list-style-type: none"> (a) holds a qualification in geotechnical engineering or equivalent; and (b) has a minimum of at least three years experience working as a geotechnical engineer.
time limited operations	refers to the operation of the infrastructure and equipment identified under this works approval that is authorised for that purpose, subject to the relevant conditions.
waste	has the same meaning given to that term under the EP Act.
works approval	refers to this document, which evidences the grant of the works approval by the CEO under section 54 of the EP Act, subject to the conditions.
works approval holder	refers to the occupier of the premises being the person to whom this

Term	Definition
	works approval has been granted, as specified at the front of this works approval.

END OF CONDITIONS

Schedule 1: Maps

Premises map

The boundary of the prescribed premises is shown in the map below (Figure 1).




Figure 1: Map of the boundary of the prescribed premises




Figure 2: Premises infrastructure locations

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)

Schedule 2: Construction details




Figure 3: TSF3 general arrangement plan - Stage 1

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 4: TSF3 Stage 1 embankment construction details

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 5: TSF3 Stage 1 underdrainage layout

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)



IR-T05 Works approval template (v6.0) (September 2022)




Figure 7: TSF3 Stage 1 underdrainage sections and details – sheet 2

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)

W6859/2023/1 (19/03/2024)
IR-T05 Works approval template (v6.0) (September 2022)




Figure 9: TSF3 decant and causeway typical sections and details

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 10: Decant water storage pond cross section and design details

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 11: TSF3 groundwater and seepage monitoring locations and details

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 12: TSF3 groundwater monitoring bore and vibrating wire piezometer design details

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 13: NLO TSF raise 5 general arrangement

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 14: NLO TSF raise 5 embankment construction details – Type A

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 15: NLO TSF raise 5 embankment construction details – Type B

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 16: NLO TSF raise 5 embankment construction details – Type C

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 17: NLO TSF raise 5 decant details

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 18: NLO TSF raise 5 underdrainage decant tower details

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 19: TSF3 Stage 2 - general arrangement plan

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)




Figure 20: TSF3 Stage 2 - embankment construction details

W6859/2023/1 (19/03/2024)

IR-T05 Works approval template (v6.0) (September 2022)

Schedule 3: Groundwater monitoring quality assurance and quality control

The works approval holder must adhere to the following field quality assurance and quality control procedures, as specified in Schedule B2 of the Assessment of Site Contamination NEPM, and must include as a minimum:

- (e) decontamination procedures for the cleaning of tools and sampling equipment before sampling and between samples;
- (f) field instrument calibration for instruments used on site;
- (g) blind replicate samples and rinsate blanks must be collected in the field and sent to the primary laboratory to determine the precision of the field sampling and laboratory analytical program;
- (h) completed field monitoring sheets / sampling logs for each sample collected, showing:
 - (i) time of collection;
 - (ii) location of collection;
 - (iii) initials of sampler;
 - (iv) sampling method;
 - (v) field analysis results;
 - (vi) duplicate type / location (if relevant); and
 - (vii) site observations and weather conditions, and
- (i) chain-of-custody documentation must be completed which details the following information:
 - (i) site identification;
 - (ii) the sampler;
 - (iii) nature of the sample;
 - (iv) collection time and date;
 - (v) analyses to be performed;
 - (vi) sample preservation method;
 - (vii) departure time from site;
 - (viii) dispatch courier(s); and
 - (ix) arrival time at the laboratory.