



## Noise regulations: Part 3—Noise measurement

### Purpose

The purpose of this fact sheet is to provide guidance for users of the *Environmental Protection (Noise) Regulations 1997* (the Regulations) in relation to Part 3—Noise measurement.

### Noise measurement

The way to establish whether a noise emission is meeting the assigned level is to carry out sound level measurements. The instrument normally used for this is a sound level meter, but special sound recorders and analysers may also be used. The science of sound measurement calls for certain rules to be put in place in order that the results will be fair and repeatable.

A noise emission level may be determined by measurement at the receiving point if other noise sources are not dominant, or by measurement at a reference position to enable calculation of the sound level at the receiver.

Measurements need to be done over a long enough period to represent the noise emission. For a constant noise, this may only need to be a few minutes while for a noise that varies over time, a longer duration (up to several hours), may be needed to capture an amount that is typical of the noise or to capture several cycles if the noise is repetitive.

The assessing officer uses the measurement results to determine the levels of the noise emission (e.g.  $L_{A\ max}$ ,  $L_{A\ 1}$  or  $L_{A\ 10}$ , as appropriate), over a representative assessment period of 15 minutes to four hours (as determined by an inspector or authorised person to be appropriate for the emission), for comparison with the assigned levels.

Note that the duration of the measurement period may differ from the representative assessment period.

### Place of measurement

When the premises receiving the noise has a building or buildings and surrounding land, the noise may be measured either outside the buildings and within the premises boundary, or inside the buildings, but can only be measured inside if:

- the use of the building is directly associated with the type of premises receiving the noise, e.g. the building is an office on a commercial premises or a house on a noise sensitive premises; and
- the building is of a type of construction that is typical of buildings so used, e.g. you would not carry out a sound measurement inside a tent, as its construction is not typical of a house.

Where the premises receiving the noise is a caravan park or camping ground, measurements are to be made outside of a caravan, camp or park home.

The measurement is taken inside where:

- there is no surrounding land, e.g. a block of units; or
- the noise is coming through a common wall or from another part of the building.

Where a measurement is made inside, the measured level is adjusted by:

- +15 dB if the external doors and windows are shut; or
- +10 dB if the external doors and windows are open.

## Microphone position

The microphone must be placed at least 1.2 metres above the ground and, if measured outdoors, at least three metres from any other sound reflecting surface, if practicable, to avoid the effect of sound reflections. Indoor measurements must be made at least one metre from any open external window or door.

Measurement of airblast levels during blasting must be done outdoors, with the microphone 1.2 to 1.6 metres above the ground and at least five metres from any other reflecting surface.

## Instrument calibration

Schedule 4 of the Regulations sets out various standards to which the sound measuring instruments must comply.

The instrument must have been calibrated in an approved laboratory within the two-year period immediately preceding its date of use, to check that its performance meets the standards.

Field performance checks must be carried out before and after measurements.

Instruments used to measure airblast levels have additional requirements for low frequency performance.

## More information

For advice on noise measurement, or related matters, please contact DER Noise Regulation on 6467 5000.

This document is available in alternative formats and other languages on request.

## Related documents

Additional publications about noise regulation are available online from [www.der.wa.gov.au/noise](http://www.der.wa.gov.au/noise) or can be requested by phoning 6467 5000.

## Legislation

This document is provided for guidance only. It should not be relied upon to address every aspect of the relevant legislation. Please refer to the State Law Publisher (SLP) for copies of the relevant legislation, available electronically from the SLP website at [www.slp.wa.gov.au](http://www.slp.wa.gov.au)

## Disclaimer

The information contained in this document is provided by DER in good faith as a public service. However, DER does not guarantee the accuracy of the information contained in this document and it is the responsibility of recipients to make their own enquiries as to its accuracy, currency and relevance. The State of Western Australia, DER and their servants and agents expressly disclaim liability, in negligence or otherwise, for any act or omission occurring in reliance on the information contained in this document or for any consequence of such act or omission.

## Limitation

The Western Australian Government is committed to providing quality information to the community and makes every attempt to ensure accuracy, currency and reliability of the data contained in this document. However, changes in circumstances after the time of publication may impact on the quality of information. Confirmation of the information may be sought from the relevant originating bodies or the department providing the information. DER and the State of Western Australia reserve the right to amend the content of this document at any time without notice.

## Legal advice

The information provided to you by DER in relation to this matter does not constitute legal advice. Due to the range of legal issues potentially involved in this matter, DER recommends that you obtain independent legal advice.